

PRODUCT DESCRIPTION

Sterilizes by infrared heat-organic material that is incinerated deep in a ceramic funnel tube Sterilizes loops and needles safely and conveniently Prevents infectious spatter and/or cross-contamination Safeguards laboratory personnel - no open flame or hazardous gas Sterilization takes only...







Features

- •Sterilizes inoculating loops,
- needles and culture tube mouths safely and conveniently,
- •preventing infectious splatter and cross-contamination, Bacti-cinerator units kill microorganisms utilizing infrared heat produced by a ceramic core element with no asbestos,
- •Ensuring sterility.
- •Flameless electric bacti-cinerator operation safeguards personnel and is ideal for anaerobic chambers.
- •Weighted base for stability.
- •On/off switch,
- pilot light and 6 needle/loop storage holes. 120V.
- •Uses infrared heat to incinerate organic material deep within the ceramic funnel
- •Sterilizes platinum loops and needles safely and conveniently
- •Prevents infectious spatter and cross contamination
- •Sterilization takes only 5 to 7 seconds at optimum sterilizing temperature of $1500\,^{\circ}\mathrm{F}$
- •Unit can be used in anaerobic chambers
- •This product is not approved or intended for, and should not be used for medical, clinical, surgical or other patient oriented applications

SPECIFICATION

MODEL	BS LS-100
Product Type	Bacterial Incinerator/Infrared Sterilizer
Frequency	50/60 Hz
Sterilization Method	Infrared heat
High Temp. Setting:	815°C/1500°F
Low Temp. Setting:	500°C/950°F
Sterilization Time:	5-7 Seconds
Chamber Diameter:	0.55 in/14mm
Chamber Length:	6.2 in/157mm
Dimensions: WxDXH	4x6x6.5 in
	10.2x15.2x16.5cm
Weight:	3 lbs (1.3kg)
Electrical:	120V, 50-60Hz 50W
Warranty:	1 Year



BIOGENIX SYSTEMS PRIVATE LIMITED

S-10, Pankaj Central Plaza, Pocket-5, Plot no-5, Sector-12, Dwarka, New Delhi-110075, INDIA

Email: sales@biogenixsystems.com | Phone: +91-11-43738899 |

9990251155-99 | 9911717057 Website: www.biogenixsystems.com