

STERILITY TEST PUMP

Brand: BioGenix®

MODEL: BS-APL-05



OVERVIEW

The function of the bacteria collection instrument is to test whether the test product contains bacteria, and it is used in conjunction with the bacteria collection incubator. Mainly used for sterility testing of sterile preparations for injection, including antibiotics and drugs containing antibacterial ingredients, large infusions, water injections, sterilized medical devices, sterile water for injection, etc.

PRODUCT FEATURES

- 1. Straight pipe installation, automatic pipe clamping** Easy to operate, effectively avoiding the risk of pinching caused by improper installation
- 2. Pump head protection cover** New design, safety protection function, prevent operator injury
- 3. Touch sensitive panel** Waterproof touch-sensitive control panel, easy to operate and durable, safe and beautiful, easy to clean
- 4. Have SOP function** Custom time, rotation speed, batch speed, can be stored and memorized



Performance Feature:

1. Compact design, less occupation of super-clean worktable space and less airflow interference.
2. VFD vacuum fluorescent screen display, dynamic running indication function, clock function
3. Stepless speed regulating, 6-speed direct regulation, with speed memory function
4. Pump head protection function, protection from operators' injury, 304 stainless steel peristaltic pump head
5. Direct driving by motor, low operating power, the temperature on the machine surface significantly decreased.
6. Waterproof design for foot pedal interface
7. The height of the hanging rod is regulated according to a height of the clean worktable



8. Glazing stainless steel enclosure, smooth surface, easy to clean and disinfect
9. Independent drainage tank design, easy to clean and maintain, equipped with the holder for valuable samples recovery holder for valuable samples recovery
10. Brushless alternating current motor, high reliability, long life, no electrical contact spark, safe and good explosion-proof property
11. Bottle-shaped ring for bottle loading, effective protection of samples, compliance with international standards

TECHNICAL SPECIFICATION:

Power supply : 110V-220V	Total height of hanger : 450mm
Dimensions : 280×407×222mm	Rated power : ≤550W
Weight : 18kg	Case material : 304
Speed : 0-330rpm	Flow under the max rotation speed : 700ml/min